



















TUEGA

















Turnstile - Gate Summary

















Turnstile - BAR

Turnstile visualization	Turnstile model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Optional power supply	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	BAR-BA	Waist tripod turnstile with two legs	Low	Fail-Lock	Brushed stainless steel	-	Fail-Safe motor / Emergency drop arm (as optional)	1 per each direction	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof / Outdoor without roof		Go call function / Emergency drop arm* / Outdoor package* / Anti-Climb sensor*
	BAR-EC BAR-EK	Waist tripod turnstile with single leg	Low	Fail-Lock	BAR-EC - powder coated zinc treated steel BAR-EK - brushed stainless steel	RAL color only for BAR-EC	Fail-Safe motor / Emergency drop arm (as optional)	One for both directions	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof		Go call function / Emergency drop arm* / Outdoor package* / Anti-Climb sensor*
	BAR-WN	Waist tripod turnstile with height adjustable legs	Low	Fail-Lock	Powder coated zinc treated steel	RAL color	Fail-Safe motor	One for both directions	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof / Outdoor without roof		Go call function / Outdoor package
	BAR EK-wall	Waist tripod turnstile without leg (mounted directly on the wall/ reception desk)	Low	Fail-Lock	Brushed stainless steel	-	Fail-Safe motor / Emergency drop arm (as optional)	One for both directions	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof		Go call function / Emergency drop arm* / Outdoor package* / Anti-Climb sensor*
	BAR ST	Waist tripod turnstile with two legs	Low	Fail-Lock	Powder coated zinc treated steel	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor / Emergency drop arm (as optional)	One per each direction	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof / Outdoor without roof		Go call function / Emergency drop arm* / Outdoor package* / Anti-Climb sensor*
	BAR ST-DUO	Double Waist tripod turnstile with two legs	Low	Fail-Lock	Powder coated zinc treated steel	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor / Emergency drop arm (as optional)	One per each lane/ direction	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof / Outdoor without roof		Go call function / Emergency drop arm* / Outdoor package* / Anti-Climb sensor*
	BAR SKR	Waist tripod turnstile with single leg	Low	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Stainless steel Tripod arms	Indoor / Outdoor with roof / Outdoor without roof		Go call function / Outdoor package*
	BAR SKR-DropArm	Waist tripod turnstile with single leg	Low	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor / Emergency drop arm	Two jumbo LED (red/ green) for both directions	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof / Outdoor without roof		Go call function / Emergency drop arm / Outdoor package*
	BAR GX	Waist tripod turnstile with full-frame cabinet	Low	Fail-Lock	Brushed stainless steel	Polished stainless steel	Fail-Safe motor / Emergency drop arm (as optional)	One per each direction	13,8 VDC	24 VAC / 230 VAC	Stainless steel Tripod arms	Indoor / Outdoor with roof		Go call function / Emergency drop arm* / Outdoor package* / Anti-Climb sensor*

















Turnstile - ROUND

Turnstile visualization	Turnstile model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Optional power supply	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	ROUND E	Half-height turnstile	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	3 wings version / Glass wing	Indoor		Logo on glass wing*
	ROUND E-S	Half-height turnstile in slim version	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	3 wings version / Glass wing	Indoor		Logo on glass wing*
	ROUND F	Half-height turnstile side glass panels	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	3 wings version / Glass wing	Indoor		Logo on glass wing*
	ROUND J	Half-height turnstile	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	3 wings version / Tubular U-arms	Indoor / Outdoor with roof / Outdoor without roof		Water Resistant version / Outdoor package*
	ROUND J-S	Half-height turnstile in slim version	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	3 wings version / Tubular U-arms	Indoor / Outdoor with roof / Outdoor without roof		Water Resistant version / Outdoor package*
	ROUND J90-U arm	Half-height turnstile	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	4 wings version / Tubular U-arms	Indoor / Outdoor with roof / Outdoor without roof		Water Resistant version / Outdoor package*
	ROUND J90-Straight	Half-height turnstile	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	4 wings version / Straight bar arms	Indoor / Outdoor with roof / Outdoor without roof		Water Resistant version / Outdoor package*
ROUND J90-Straight 1300		Half-height turnstile in extended height version (turnstile height 1300 mm) - all other features are the same as for ROUND J90-Straight turnstile												
	ROUND J90-DUO-Straight	Double half-height turnstile	Middle	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	4 wings version / Straight bar arms	Indoor / Outdoor with roof / Outdoor without roof		Water Resistant version / Outdoor package*
ROUND J90-DUO-Straight 1300		Double half-height turnstile in extended height version (turnstile height 1300 mm) - all other features are the same as for ROUND J90-DUO-Straight turnstile												













Turnstile - REXON ERA

Turnstile visualization	Turnstile model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Optional power supply	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	REXON ERA 3	3-wings full-height turnstile	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package
	REXON ERA 4	4-wings full-height turnstile	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	4 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package
	REXON ERA 4-LE	4-wings full-height turnstile with front/rear panels	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	4 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Front-Rear panels
	REXON ERA 3-GS-U	3-wings full-height turnstile with side glass panels	High	Fail-Lock	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Tubular U-arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Glass side panels
	REXON ERA DUO 3	Double 3-wings full-height turnstile	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / RAL color	Fail-Safe motor	One per each lane/direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package
	REXON ERA DUO 4-LE	Double 4-wings full-height turnstile with front/rear panels	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each pass/direction in special bracket	13,8 VDC	24 VAC / 230 VAC	4 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side-Back panels
	REXON ERA 3 GATE-Bike	3-wings full-height turnstile with integrated gate for bicycles	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Glass version

Turnstile - REXON DEA

Turnstile visualization	Turnstile model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Optional power supply	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	REXON DEA	3-wings full-height turnstile with side panels and canopy	High	Fail-Lock	Powder coated frame/roof, zinc treated central pillar with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof
	REXON DEA-U	3-wings full-height turnstile with side panels and canopy	High	Fail-Lock	Powder coated frame/roof, polished stainless steel central pillar with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Tubular U-arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof
	REXON DEA DUO	Double 3-wings full-height turnstile with side panels and canopy	High	Fail-Lock	Powder coated frame/roof, zinc treated central pillar with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each lane/direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof
	REXON DEA GATE-Bike	3-wings full-height turnstile with side panels and canopy with integrated gate for bicycles	High	Fail-Lock	Powder coated frame/roof, zinc treated central pillar with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof / Gate for bicycles
	REXON DEA GATE-Bike-U	3-wings full-height turnstile with side panels and canopy with integrated gate for bicycles	High	Fail-Lock	Powder coated frame/roof, polished stainless steel central pillar with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Tubular U-arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof / Gate for bicycles
	REXON DEA GATE-Full	3-wings full-height turnstile with side panels and canopy with integrated Full-height gate (wheelchair access)	High	Fail-Lock	Powder coated frame/roof, zinc treated central pillar with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each lane/direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof / Full-height gate (wheelchair access)
	REXON DEA GATE-Full-U	3-wings full-height turnstile with side panels and canopy with integrated Full-height gate (wheelchair access)	High	Fail-Lock	Powder coated frame/roof, polished stainless steel central pillar with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each lane/direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Tubular U-arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof / Full-height gate (wheelchair access)
	REXON DEA GLASS	3-wings revolving glass full-height turnstile	High	Fail-Lock	Brushed stainless steel frame with glass, glass wings	Polished stainless steel	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	3 wings version / Glass wings	Indoor		Extra brake mechanism / Outdoor package / Glass version







GATE ERA / DEA

Gate visualization	Gate model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Optional power supply	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	GATE ERA	Additional full-height gate for REXON ERA turnstile	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Full-height gate (wheelchair access)
	GATE ERA-U	Additional full-height gate for REXON ERA turnstile	High	Fail-Lock	Zinc treated steel, polished stainless steel rotor with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	Tubular U-arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Full-height gate (wheelchair access)
	GATE ERA DUO	Additional double full-height gate for REXON ERA turnstile	High	Fail-Lock	Zinc treated steel	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Full-height gate (wheelchair access)
	GATE ERA DUO-U	Additional double full-height gate for REXON ERA turnstile	High	Fail-Lock	Zinc treated steel, polished stainless steel rotor with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	Tubular U-arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Full-height gate (wheelchair access)
	GATE DEA DUO	Additional double full-height gate with side panels and canopy for REXON DEA turnstile	High	Fail-Lock	Powder coated frame/roof, zinc treated rotor with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	Straight bar arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof / Full-height gate (wheelchair access)
	GATE DEA DUO-U	Additional double full-height gate with side panels and canopy for REXON DEA turnstile	High	Fail-Lock	Powder coated frame/roof, polished stainless steel rotor with arms	Brushed stainless steel / Polished stainless steel / RAL color	Fail-Safe motor	One per each direction in special bracket	13,8 VDC	24 VAC / 230 VAC	Tubular U-arms	Indoor / Outdoor		Extra brake mechanism / Outdoor package / Side panels and roof / Full-height gate (wheelchair access)







Swing Gate - PEGAS

Gate visualization	Gate model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Optional power supply	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	PEGAS GL	Swing Gate with glass wing	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Glass wing	Indoor		Opening angle in range 0°-270° for each direction / Logo on glass wing*
	PEGAS GL-M	Swing Gate with glass wing with push-bar	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Glass wing	Indoor		Opening angle in range 0°-270° for each direction / Logo on glass wing*
	PEGAS GLE	Swing Gate with glass wing with limited opening angle	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Glass wing	Indoor		Opening angle up to 90° only / Logo on glass wing* / Top panel for Radar or Proxy reader*
	PEGAS GLE-M	Swing Gate with glass wing with limited opening angle and with push-bar	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Glass wing	Indoor		Opening angle up to 90° only / Logo on glass wing* / Top panel for Radar or Proxy reader*
	PEGAS SF	Swing Gate with stainless steel wing	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Stainless steel U-frame wing	Indoor / Outdoor		Water Resistant version / Opening angle in range 0°-270° for each direction / Outdoor package* / Top panel for Radar or Proxy reader*
	PEGAS SF-S	Swing Gate with stainless steel wing and infill glass panel	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Stainless steel wing U-frame with infill glass panel	Indoor / Outdoor		Water Resistant version / Opening angle in range 0°-270° for each direction / Outdoor package* / Logo on glass wing* / Top panel for Radar or Proxy reader*
	PEGAS J	Swing Gate with stainless steel wing	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Stainless steel U-frame wing	Indoor / Outdoor		Water Resistant version / Opening angle in range 0°-270° for each direction / Outdoor package* / Top panel for Radar or Proxy reader*





Swing Gate - PEGAS

Gate visualization	Gate model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Optional power supply	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	PEGAS GLE for EasyGate LX 1200	Swing Gate with 1200mm height glass wing with limited opening angle	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Glass wing	Indoor		Opening angle up to 90° only / Logo on glass wing* / Top panel for Radar or Proxy reader*
	PEGAS GLE for EasyGate LX 1800 (tandem gate required)	Swing Gate with 1800mm height glass wing with limited opening angle	Low	Fail-Safe	Brushed stainless steel	Polished stainless steel / RAL color	Fail-Safe motor	Only on external post	13,8 VDC	-	Glass wing	Indoor		Opening angle up to 90° only / Logo on glass wing* / Top panel for Radar or Proxy reader*
	Tandem gate	Double gate for extra-wide passage width	Low	Fail-Safe	All the features depends on used gate type									
	Pegas Top	White plexiglass top module for integration of motion radar (free exit) or proximity reader			Including radar/proxy reader bracket. Available for PEGAS gate GLE, GLE-M, SF, SF-S, J. All the gate features depends on used gate type.									

















Turnstile - EASYGATE LX, FL

Turnstile visualization	Turnstile model	General description	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Emergency device	Traffic light (as optional)	Standard power supply	Max. passage width	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	EasyGate LX 1200	Security sliding gate turnstile	Middle	Fail-Safe only	Brushed stainless steel	RAL color / Toplid: marble, corian, wood, glass	Fail-Safe motor	Direction (front) / Access (on the top)	24 VAC	970 mm	1200mm high glass wing	Indoor / Outdoor with roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Card collector* / Housing for Bar code scanner*
	EasyGate LX 1800	Security sliding gate turnstile	High	Fail-Safe only	Brushed stainless steel	RAL color / Toplid: marble, corian, wood, glass	Fail-Safe motor	Direction (front) / Access (on the top)	24 VAC	970 mm	1800mm high glass wing	Indoor / Outdoor with roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Card collector* / Housing for Bar code scanner*
For EasyGate LX 1200 / EasyGate LX 1800 turnstile: the multi-lane configuration is available														
	EasyGate FL	Security gate turnstile with scissors glass wing opening	Middle	Fail-Safe only	Brushed stainless steel	RAL color / Toplid: marble, corian, wood, glass	Fail-Safe motor	Direction (front) / Access (on the top)	24 VAC	980 mm	scissors glass wing	Indoor / Outdoor with roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Card collector* / Housing for Bar code scanner*
For EasyGate FL turnstile: the multi-lane configuration is available														

Turnstile - EASYGATE HG

Turnstile visualization	Turnstile model	General description	Turnstile type	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Traffic light (as optional)	Standard power supply	Max. passage width	Barrier type	Installation environment	Traffic type	Other features (* optional)
	EasyGate HG - 1wing	Security swing gate turnstile	1 wing technology / customized wing height of 1200 mm - 1800 mm	High	Fail-Safe only	Brushed stainless steel	RAL color / Toplid: marble, corian, wood, glass	Direction (front) / Access (on the top)	13,8 VDC / (24 VAC as optional)	600 mm	Glass wing with height of 1200 mm - 1800 mm	Indoor / Outdoor with roof		Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Card collector* / Logo on glass wing*
	EasyGate HG - 2wings	Security swing gate turnstile	2 wings technology / customized wing height of 1200 mm - 1800 mm	High	Fail-Safe only	Brushed stainless steel	RAL color / Toplid: marble, corian, wood, glass	Direction (front) / Access (on the top)	13,8 VDC / (24 VAC as optional)	1 100 mm	Glass wing with height of 1200 mm - 1800 mm	Indoor / Outdoor with roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Card collector* / Logo on glass wing*
For all EasyGate HG turnstiles: the multi-lane configuration is available														

Turnstile - EASYGATE SG, SH

Turnstile visualization	Turnstile model	General description	Turnstile type	Security level	Standard type of motor drive unit	Standard housing material	Optional housing material	Traffic light (as optional)	Standard power supply	Max. passage width	Barrier Type	Installation environment	Traffic type	Other features (* optional)
	EasyGate SG 1000 - 1 wing	Security swing door turnstile	1 wing technology / 1000mm long rounded cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Access (on the top)	13,8 VDC	550 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*
	EasyGate SH 1000 - 1 wing	Security swing door turnstile	1 wing technology / 1000mm long angular cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Access (on the top)	13,8 VDC	550 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*
	EasyGate SG 1000 - 2 wings	Security swing door turnstile	2wings technology / 1000mm long rounded cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Access (on the top)	13,8 VDC	920 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*
	EasyGate SH 1000 - 2 wings	Security swing door turnstile	2wings technology / 1000mm long angular cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Access (on the top)	13,8 VDC	920 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*
	EasyGate SG 1600 - 2 wings	Security swing door turnstile	2wings technology / 1600mm long rounded cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Access (on the top)	13,8 VDC	1 200 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*
	EasyGate SH 1600 - 2 wings	Security swing door turnstile	2wings technology / 1600mm long angular cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Direction (front) / Access (on the top)	13,8 VDC	1 200 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*
	EasyGate SG 2000 - 2 wings	Security swing door turnstile	2wings technology / 2000mm long rounded cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Access (on the top)	13,8 VDC	1 200 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*
	EasyGate SH 2000 - 2 wings	Security swing door turnstile	2wings technology / 2000mm long angular cabinet	Middle	Fail-Safe only	Brushed stainless steel	RAL color / TopLid: marble, corian, wood, glass	Direction (front) / Access (on the top)	13,8 VDC	1 200 mm	Glass wing / Stainless steel tube wing	Indoor / Outdoor with roof / Outdoor without roof		Wheelchair access / Outdoor package* / Proximity reader bracket* / Housing for Bar code scanner* / Logo on glass wing*

For all EasyGate SG / EasyGate SH turnstiles: the multi-lane configuration is available

TUEGA



LEGEND:

- Fail-Lock motor - locked without power
- Fail-Safe motor - free-to-move without power



V. Antonelli 4/a - 10093 Collegno (TO) Tel. 011 749.39.39 - 771.03.34 - 748.702 - 750.96.28 Fax. 011 757.63.11
www.tuega.com - info@tuega.com